

Data sheet

Mini Jumper, Shunt, 2.54 mm, open, 6.00 mm height

Page 1/2

P/N
09200-71-BBGB002025/08/28
Version: B

Illustrations



See enlarged drawings at the end of document

Product specification

- Insulator: PBT +30% Glass fiber
- Contact Pin: Brass
- Current Rate: 3 AMP
- Insulation Resistance: 5000 MOhm min. at DC 500 V
- Contact Resistance: 20 mOhm max. at DC 100 mA
- Dielectric Voltage: 500 V AC for one minute
- Operation Temperature: -55 °C to 105 °C
- Plating: Gold Flash



Data sheet

Page 2/2

Mini Jumper, Shunt, 2.54 mm, open, 6.00 mm heightP/N
09200-71-BBGB002025/08/28
Version: B**Technical Data****Application note**

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).

