

# Data sheet

## E-DAT Industry IP67 V6 plug

Page 1/7

P/N  
130906-03-E

EAN 4250184105381


2025/09/17

Version: A

### Illustrations



Dimensional drawing



See enlarged drawings at the end of document

### Product specification

- Cat.6 class E<sub>A</sub> plug in plug housing according to standard IEC 61076-3-106 Var. 6
- compliance with class E<sub>A</sub> according to ISO/IEC 11801, DIN EN 50173-1
- suitable for 10 GBit Ethernet(IEEE 802.3an) and Remote Powering(PoE, PoE plus and UPoE) and HDBaseT
- complies with ingress protection IP67 when plugged in
- AWG 27/7 - 24/7 and AWG 24/1 connection possible
- solid copper wire diameter from 0.36 to 0.51 mm
- stranded copper wire diameter from 0.46 to 0.61 mm
- conductor diameter from 0.85 to 1.05 mm
- cable jacket diameter 5.5 to 6.2 mm can be connected
- large 360° shield contact
- locking clip can also be upgraded in its installed state
- protected against unintentional opening by means of locking clip (also colored)
- crimping of the internal and external conductors with professional crimp pliers in one process
- professional crimping tool available in the tools section



**Data sheet**  
**E-DAT Industry IP67 V6 plug**

P/N  
**130906-03-E**  
**EAN 4250184105381**  
 2025/09/17  
 Version: A

**Technical Data**

**General Data**

|   |                                   |
|---|-----------------------------------|
| Fields of application                         | Industrial Ethernet               |
| Mechanical measurement according to MICE      | M1                                |
| Ingress measurement according to MICE         | I1                                |
| Climatic measurement according to MICE        | C1                                |
| Electromagnetic measurement according to MICE | E2                                |
| Design  | plug                              |
| Transmission technology                       | Copper                            |
| Color   | light gray                        |
| Dimensions                                    |                                   |
| Dimension (L x W x H)                         | 59.5 mm x 47.3 mm x 21.9 mm       |
| Dimension (L x W x H)                         | 2.343 in. x 1.862 in. x 0.862 in. |
| Labeling option                               | on housing                        |

**Transmission characteristics**

|                                 |                |
|---------------------------------|----------------|
| Category (ISO)                  | 6              |
| Class (ISO/IEC)                 | E <sub>A</sub> |
| Category (TIA)                  | 6              |
| Remote Powering                 | yes            |
| PoE                             | IEEE 802.3af   |
| PoE plus                        | IEEE 802.3at   |
| UPoE                            | yes            |
| HDBaseT                         | yes            |
| Transmission rate up to 10 GBit | IEEE 802.3an   |

**Connections/interfaces**

|  |                |
|--|----------------|
| Connector technology interface 1         | IDC-connection |
| Connector technology interface 2         | RJ45 plug      |
| Number of ports interface 2              | 1              |
| Number of ports interface 2 equipped     | 1              |
| Number of positions/contacts interface 1 | 8              |
| Number of positions/contacts interface 2 | 8P/8C          |
| Protective housing interface 1           | V6             |
| Protective housing interface 2           | V5             |

## Technical Data

### Connections/interfaces

Termination data, solid wire (min. - max.)

|  |                       |
|--|-----------------------|
| Conductor cross section, solid wire          | AWG 24/1              |
| Conductor cross section, solid wire          | 0.205 mm <sup>2</sup> |
| Conductor diameter, solid wire (bare copper) | 0.511 mm              |
| Conductor diameter, solid wire (bare copper) | 0.02 in.              |

Termination data, stranded wire (min. - max.)

|   |   |
|---|---|
| Conductor cross section, stranded wire          | AWG 27/7 - AWG 24/7                           |
| Conductor cross section, stranded wire          | 0.111 mm <sup>2</sup> - 0.227 mm <sup>2</sup> |
| Conductor diameter, stranded wire (bare copper) | 0.457 mm - 0.61 mm                            |
| Conductor diameter, stranded wire (bare copper) | 0.018 in. - 0.024 in.                         |

Aderdurchmesser (min.-max.)

|   |                      |
|---|----------------------|
| Core diameter (conductor with insulation) | 0.85 mm - 1.02 mm    |
| Core diameter (conductor with insulation) | 0.033 in. - 0.04 in. |

Cable sheath diameter (min. - max.)

|                       |                   |
|-----------------------|-------------------|
| Cable sheath diameter | 5.5 mm - 6.20     |
| Cable sheath diameter | 0.217 in. - 0.244 |

|                     |      |
|---------------------|------|
| Cable access/outlet | 180° |
|---------------------|------|

### Electrical characteristics

|   |                |
|---|----------------|
| Contact resistance                                  | max. 20 mOhm   |
| Insulation resistance                               | min. 500 MOhm  |
| Dielectric strength conductor-conductor (secondary) | min. 1000 V DC |

### Mechanical data

|                                     |               |
|-------------------------------------|---------------|
| Locking method (protective housing) | locking clamp |
|-------------------------------------|---------------|

### Materials and material properties

|                                    |                                |
|------------------------------------|--------------------------------|
| Material - Housing                 | PC UL94 V0                     |
| Material - Protective housing      | PA 6.6 UL94 V0                 |
| Material - Contact                 | PhBr (phosphor bronze)         |
| Material - Contact finish          | Ni + Au (nickel-gold)          |
| Material - Shield                  | CuZn                           |
| Material - Shield finish           | Ni (nickel)                    |
| Material - Protective housing seal | NBR (nitrile butadiene rubber) |



# E-DAT Industry IP67 V6 plug

P/N

130906-03-E

EAN 4250184105381

2025/09/17

Version: A

## Technical Data

### Materials and material properties

|                    |             |
|--------------------|-------------|
| Material - Cap nut | PA UL 94 V0 |
| Halogen free       | yes         |
| RoHS               | compliant   |

### Environmental conditions

|                            |   |
|----------------------------|---|
| Temperature (min. - max.)  |   |
| Temperature - Storage °C   | -40 °C - 70 °C  |
| Temperature - Storage °F   | -40 °F - 158 °F   |
| Temperature - Operating °C | -40 °C - 70 °C  |
| Temperature - Operating °F | -40 °F - 158 °F   |
| Particulate ingress        | IP6X with protective housing  |
| Liquid ingress/immersion   | IPX7 with protective housing  |
| General information        | This product is suitable for use in industrial environments inside buildings with IPxy protection class according to DIN EN 60529 specified in this data sheet. Not specified for outdoor applications. |

### Standards/Regulations

|  |  |
|--|--|
| Generic cabling systems  |  |
| General requirements   | ANSI/TIA-568-C   |
| Office buildings   | ISO/IEC 11801 Ed.2.2: 2011-06   DIN EN 50173-2<br>ANSI/TIA-568-C |
| Industrial area  | ISO/IEC 24702   DIN EN 50173-3<br>ANSI/TIA-1005                  |
| Living units   | ISO/IEC 15018   DIN EN 50173-4<br>ANSI/TIA-570-B                 |
| Connectors for electronic equipment  |  |
| Rectangular connectors   | DIN EN 61076-3-106   |
| Connectors for electronic equipment - Tests and measurements                           |  |
| Degrees of Protection Provided by Enclosures   | IEC 60529  |
| Interference proof   |  |
| Immunity for industrial environments   | DIN EN 61000-6-2:2006-03   |
| Emission proof   |  |
| Electromagnetic emission for residential, commercial and light-industrial environments | DIN EN 61000-6-3:2011-09   |

Data sheet  
E-DAT Industry IP67 V6 plug

Page 5/7

P/N  
130906-03-E  
EAN 4250184105381  
2025/09/17  
Version: A

## Technical Data

### Classifications

|           |          |
|-----------|----------|
| ETIM 7.0  | EC001121 |
| ETIM 8.0  | EC001121 |
| ETIM 9.0  | EC001121 |
| ETIM 10.0 | EC001121 |

### Packing details

Type of packaging 1 pc(s) / plastic bag

### Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).



Data sheet  
E-DAT Industry IP67 V6 plug

Page 6/7

P/N  
130906-03-E  
EAN 4250184105381  
2025/09/17  
Version: A

## Accessories

| P/N         | Designation                                    |
|-------------|--|
| 130906-V3-I | Locking clamp for IP67 V6 plug, light gray     |
| 130906-V5-I | Locking clamp for IP67 V6 plug, yellow         |
| 130906-V6-I | Locking clamp for IP67 V6 plug, blue           |
| 130906-V7-I | Locking clamp for IP67 V6 plug, green          |
| 130906-V8-I | Locking clamp for IP67 V6 plug, red            |
| 130907-E    | Crimp pliers for E-DAT Industry IP20 RJ45 plug |

Data sheet  
**E-DAT Industry IP67 V6 plug**

Page 7/7

P/N  
**130906-03-E**  
EAN 4250184105381  
2025/09/17  
Version: A

**Illustrations**

Dimensional drawing

