

Data sheet

OpDAT VADT plug-in 4xLC/LC OM3


Page 1/5

P/N
150M045HJJXXE


2025/06/11

Version: H

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- compact fiber optic termination unit for flush mounted outlets or cavity wall boxes
- Box ready for installation, pre-terminated with multimode indoor cable and equipped with adapters for the connection of up to four fiber optic patch cables.
- The second cable end is pre-assembled with fiber optic plugs, plug type selectable. To protect these connectors, nubbed foil or a retractable aid with IP50 is available.
- cable easy to mount on carton drum
- cable type: mini breakout cable, Ø 5.2 mm
- Available with laser-optimized, bend-insensitive multimode fibers:
- OM3, G50/125 µm, according to IEC 60793-2-10 Typ A1a.2
- OM4, G50/125 µm, according to IEC 60793-2-10 Typ A1a.3
- OM5, G50/125 µm, according to IEC 60793-2-10 Typ A1a.4
- supplied with fixing material
- color box pure white (similar to RAL 9010)
- cable lengths: 2 to 100 m
- (replace XX in the part number by the length, for example 05=5 m, A0=100 m)
- all available variants can be created with the VADT configurator



Data sheet

Page 2/5

OpDAT VADT plug-in 4xLC/LC OM3

P/N
150M045HJJXXE

2025/06/11

Version: H

Technical Data

General Data

Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	wall outlet
Mounting style	AP
Transmission technology	Fiber optic
Color	white
Dimensions	
Dimension (L x W x H)	85 mm x 100 mm x 35 mm
Dimension (L x W x H)	3.346 in. x 3.937 in. x 1.378 in.
Mode type of the fiber	Multimode
Fiber class	OM3
Fiber construction	50/125 µm

Connections/interfaces

Connector technology interface 1	LC
Connector technology interface 2	LC
Number of ports interface 1	4
Number of ports interface 2	4
Number of equipped ports interface 1	4
Number of ports interface 2 equipped	4
Number of blind	2
Cable sheath diameter (min. - max.)	
Cable sheath diameter	5.20
Cable sheath diameter	0.205

Electrical/ optical properties

Insertion loss	max. 0,2 dB
Return loss	min. 35 dB



Data sheet

Page 3/5

OpDAT VADT plug-in 4xLC/LC OM3

P/N
150M045HJJXXE

2025/06/11

Version: H

Technical Data

Mechanical data

strain relief aramide fibres

Materials and material properties

Material - Housing	Plastics
Material - Coupler housing	Plastics
Material - Sleeve	ceramic, slotted
Flame retardancy	yes
Halogen free	yes
RoHS	compliant

Standards/Regulations

Generic cabling systems	
General requirements	ISO/IEC 11801-1
Lichtwellenleiter: LWL-Innenkabel	
Sectional specification for classÂ B single-mode fibres	ISO/IEC 60793-2-10 (A1a.2)
Optical fibers - Interconnecting devices and passive components - basic test and measuring methods	
Fibre optic interconnecting devices and passive components - Insertion loss	IEC 61300-3-4
Fibre optic interconnecting devices and passive components - Return loss	IEC 61300-3-6
Fibre optic interconnecting devices and passive components - Visual inspection of plug end face	IEC 61300-3-35
ITU-T standard	ITU-T G.651.1

Classifications

ETIM 7.0	EC001409
ETIM 8.0	EC001409

Packing details

Type of packaging 1 pc(s) / box

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).



Data sheet

Page 4/5

OpDAT VADT plug-in 4xLC/LC OM3**P/N**
150M045HJJXXE

2025/06/11

Version: H

Accessories

P/N	Designation
151J1EOJXXE	OpDAT patch cord SC-D/LC-D OM3
151J1JOJXXE	OpDAT patch cord LC-D/LC-D OM3

Data sheet

Page 5/5

OpDAT VADT plug-in 4xLC/LC OM3

P/N
150M045HJJXXE

2025/06/11

Version: H

Illustrations

Dimensional drawing

