

Data sheet

MB-DIO4/2-IP Modbus/BACnet 24V AC/DC

Page 1/7

P/N
1108121326IP

EAN 4251394658360


2025/08/20

Version: I


Illustrations



Wiring diagram



Principle diagram



See enlarged drawings at the end of document

Product specification

The MB-DIO4/2-IP 24 V module in IP65 housing with 4 digital inputs, as well as 2 relay outputs, is suitable for the inclusion of decentralized signal contacts and the control of decentralized switching tasks. As signal contacts, e.g. window contacts or the positions of ventilation flaps, etc. can be detected and controlled for switching tasks, e.g. motorized actuators or light bands, etc. Actuators with AMP connectors (AMP brand from TE Connectivity) can be connected directly to the MB-DIO4/2-IP 24 V. Depending on the operating mode, the module can be switched or requested with Modbus standard registers or with BACnet objects.

- for the control of up to two actuators, e.g. fire dampers
- Connection options for actuators with AMP plug-in connector or open connection lines with pluggable push-in technology
- Supply voltage is also switching voltage
- Relay output suitable for inrush current 65 A < 20 ms (NO), continuous current 6A, total current 8A
- generous space for installation - no additional distribution box required



Data sheet
MB-DIO4/2-IP Modbus/BACnet 24V AC/DC

P/N
1108121326IP
EAN 4251394658360
 2025/08/20
 Version: I

Technical Data

Approvals



BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International (BI). BTL is a registered trademark of BI.

RS485 interface

| | |
|-----------------------------------|--|
| Protocol | Modbus RTU / BACnet MS/TP |
| Address range | 00 - EF |
| Bus interface | RS485 two wire bus with potential equalization in bus or line topology terminate with 120 Ohm |
| Transmission parameters | |
| Transmission rate | min. 1200 Bit/s (Bd) max. 115200 Bit/s (Bd) |
| Transmission rate default setting | 19200 Bit/s (Bd) |
| Parity | Odd Even (default setting) None |
| Stopbits | 1 (default setting) 2 |

Supply

| | |
|---------------------|----------------------------|
| Operating voltage | 24 V AC/DC +/- 10 % (SELV) |
| Duty cycle relative | 100 % |

Inputs

| | |
|----------------|---|
| Digital inputs | 4 |
|----------------|---|

Outputs

| | |
|---------------------------------------|-------------------------------------|
| Digital outputs | 2 |
| Relay output | 2 changeover contacts |
| Switching voltage relay output (max.) | 24 V AC |
| Continuous current relay output | 6 A / relay |
| Switch-on current relay output (max.) | 65 A < 20 ms (NO) |
| Total current across all outputs | 8 A |
| Mechanical life | 10x10 ⁶ switching cycles |
| Electrical life | 10x10 ⁴ switching cycles |

MB-DIO4/2-IP Modbus/BACnet 24V AC/DC

P/N

1108121326IP

EAN 4251394658360

2025/08/20

Version: I

Technical Data

Insulation coil - contact set

| | |
|--|--|
| Nominal voltage of the power supply system | 24V AC/DC = Operating voltage |
| Overvoltage category | III II |
| Degree of pollution | 2 2 |
| Rated test voltage | 4 kV 2.5 kV |
| Type of insulation | basic insulation reinforced insulation |

Housing

| | |
|-----------------------|---|
| Dimensions | |
| Dimension (W x H x D) | 175 mm x 175 mm x 75 mm |
| Dimension (W x H x D) | 6.89 in. x 6.89 in. x 2.953 in. |
| Weight | 630.7 g |
| Mounting style | directly on a flat base, knock-out openings for screw connections 4 x M16/25 + 14 x M12/20 |
| Mounting position | any |
| Indicator | green, red and yellow LED |

Terminal blocks

| | |
|---|---|
| Connection type 1 | Pluggable spring clamp terminal block |
| Terminal block (bus) | 6-pole |
| Terminal block (motor) | 2 x 3-pole |
| Connection terminal (digital inputs, potential-free limit switches) | 2 x 6-pole |
| Solid wire (AWG) | max. 12 AWG |
| Stranded wire (mm ²) | max. 2.5 mm ² |
| Stranded wire (AWG) | max. 12 AWG |
| Wire diameter | min. 0.25 mm max. 2.5 mm |
| Wire cross section solid | 0.2 mm ² - 2.5 mm ² / AWG 22-12 |
| Wire cross section multi | 0.2 mm ² - 2.5 mm ² / AWG 22-12 |
| Wire cross section with wire ferrule | 0.2 mm ² - 2.5 mm ² / AWG 22-12 |
| Stripping length (min.) | 10 mm |
| Connection type 2 | AMP pin header (Mate-N-Lok) |
| Pin header connection (motor) | 3-pole (TE Connectivity 1-770170-1) |
| Pin header connection (digital inputs, potential-free limit switches) | 6-pole (TE Connectivity 1-770178-1) |
| Hinged cable glands | e.g. KVT 20 with cable grommets KT 6 (6 mm) and KT 8 (8mm) from icotek (R) |



Technical Data

Terminal blocks

| | |
|---------------------------------------|---|
| Connection type 3 | screw type terminal block |
| Terminal block (protective conductor) | 3x 1-pole |
| Wire cross section solid | 0.2 mm ² - 1.5 mm ² / AWG 22-16 |
| Wire cross section multi | 0.2 mm ² - 1.5 mm ² / AWG 22-18 |
| Wire cross section with wire ferrule | 0.2 mm ² - 1.5 mm ² / AWG 22-18 |
| Screw torque (max.) | 0.5 Nm |
| Stripping length (min.) | 6 mm |
| Protection circuit | Polarity reversal protection for DC operating voltage |

Material

| | |
|---------------------------|-----------------|
| Material - Housing | Polycarbonat |
| Color | gray |
| Material - Terminal block | Polyamid 6.6 V0 |

Protection category according to IEC 60529

| | |
|---|-------------------------------|
| Protection category - housing (acc. to IEC 60529) | IP65 (without screw fittings) |
| Protection category - terminal blocks (acc. to IEC 60529) | IP20 |

Climatic Data

| | |
|----------------------------|--------------------------|
| Operating | |
| Temperature - Operating °C | -5 °C - 55 °C |
| Temperature - Operating °F | 23 °F - 131 °F |
| Relative humidity | max. 85 % non-condensing |
| Storage | |
| Temperature - Storage °C | -20 °C - 70 °C |
| Temperature - Storage °F | -4 °F - 158 °F |

Classifications

| | |
|-----------|----------|
| ETIM 7.0 | EC001584 |
| ETIM 8.0 | EC001584 |
| ETIM 9.0 | EC001584 |
| ETIM 10.0 | EC001584 |

Data sheet

Page 5/7

MB-DIO4/2-IP Modbus/BACnet 24V AC/DC

P/N

1108121326IP

EAN 4251394658360

2025/08/20

Version: I

Technical Data**Software and additional documents**

Software and documentation

Further documentation is available for free download at www.metz-connect.com**Application note**

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).



Data sheet

Page 6/7

MB-DIO4/2-IP Modbus/BACnet 24V AC/DC

P/N

1108121326IP

EAN 4251394658360

2025/08/20

Version: I

Accessories

| P/N | Designation |
|------------|--|
| 110561 | Power supply NG4 24 V DC |
| 11056170 | Power supply NG4-F 24 V DC |
| 11083001 | MR-GW Modbus RTU / Modbus TCP Gateway |
| 1108300170 | MR-F-GW Modbus RTU / Modbus TCP Gateway |
| 11088001 | BMT-RTR BACnet-Router |
| 1108800170 | BMT-F-RTR BACnet-Router |
| 11088101 | BMT-RTR/SC BACnet/SC Router |
| 1108810170 | BMT-F-RTR/SC BACnet/SC Router |




Data sheet
MB-DIO4/2-IP Modbus/BACnet 24V AC/DC

Page 7/7

P/N
1108121326IP
EAN 4251394658360
2025/08/20
Version: I

Illustrations

Wiring diagram



Principle diagram

