

Data sheet

OpDAT slide² K patch panel Prefab 6xSC-D OS2 gray

Page 1/5

P/N

150490E206-F

EAN 4251394688855


2025/10/09

Version: B

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- 19-inch, 1RU patch panel with pull-out drawer
- 30 % shorter than OpDAT slide²
- Equipped with 6xSC-D couplers
- Offset coupling arrangement for easy handling
- Tool-free metal bayonet catch for locking the drawer
- Drawer can be tilted and completely removed for easier installation (pull-out stop)
- Depth adjustable by 30 mm
- Front panel with labelling field
- Front panel powder-coated in gray RAL 7035
- Several possibilities for inclined cable entry on the back: 4xM20 (for splice variant), 4xPrefab installation cut-outs (for Prefab variant)
- Prepared for the installation of pre-assembled cables



Data sheet
OpDAT slide² K patch panel Prefab
6xSC-D OS2 gray

Technical Data

General Data

Fields of application	data center office areas structured building cabling interior Distributed building services
Features variant	Prefab
Design	Eithdrawable short
Mounting style	screwable
Transmission technology	Fiber optic
Port numbering	yes
Color housing	metal
Color front plate	RAL 7035 - light gray
Adapter color	blue
Dimensions	
Dimension (L x W x H)	183 mm x 483 mm x 44 mm
Dimension (L x W x H)	7.205 in. x 19.016 in. x 1.732 in.
Inches	19 inches
Height unit	1RU
Installation depth	169 mm
Installation depth	6.654 in.
Fiber class	OS2
Mode type of the fiber	Singlemode
Shape	UPC (Ultra Physical Contact)
Labeling option	label strip / labeling strip

Connections/interfaces

Adapter type	SC-D
Adapter interface outside	SC-D
Adapter interface inside	SC-D
Number of adapters	6
Number of breakouts front panel	12
Number of blind	6
Cable access/outlet	several possibilities for inclined cable entry on the back

Data sheet
**OpDAT slide² K patch panel Prefab
 6xSC-D OS2 gray**

Technical Data

Mechanical data

Cut-out	SC-D/LC-Q/ST-D
strain relief	optional

Materials and material properties

Material - Housing	sheet steel
Material - Housing finish	Zn (zinc)
Material - Front cover	sheet steel
Material - Front cover finish	powder-coated
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics

Standards/Regulations

FO connector interfaces	SC - IEC 61754-4
-------------------------	------------------

Classifications

ETIM 8.0	EC001130
ETIM 9.0	EC001130
ETIM 10.0	EC001130

Packing details

Type of packaging	1 pc(s) / box
-------------------	---------------

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).

Data sheet
**OpDAT slide² K patch panel Prefab
6xSC-D OS2 gray**

Page 4/5

P/N
150490E206-F
EAN 4251394688855
2025/10/09
Version: B

Accessories

P/N	Designation
150240M20Z-E	OpDAT strain relief M20
150240M25Z-E	OpDAT strain relief M25
150240Z20Z-E	OpDAT strain relief for M20
1509010000-E	OpDAT splice tray for 12 splices, unequipped
1509010001-E	OpDAT splice tray with 1 crimp protection cover
1509010002-E	OpDAT splice tray with 2 splice protection cover
15090200-E	OpDAT cover for splice tray

Data sheet

**OpDAT slide² K patch panel Prefab
6xSC-D OS2 gray**

Page 5/5

P/N

150490E206-F

EAN 4251394688855

2025/10/09

Version: B

Illustrations

Dimensional drawing

