


# Data sheet

## OpDAT fix<sup>2</sup> patch panel Prefab 48xLC-D APC OS2 gray


Page 1/5

P/N  
1504807648-E  
EAN 4251394679419  
2025/10/09  
Version: F

### Illustrations



Dimensional drawing



See enlarged drawings at the end of document

### Product specification

- 19 inch, 2RU patch panel for fixed installation
- Equipped with 48xLC-D APC couplers
- Offset coupler arrangement for easy handling
- Front panel with labelling field
- Front panel powder-coated in gray RAL 7035
- Tool-free opening of the cover
- Several possibilities for cable entry on the back: 6xM20; 2xM25; 2xPrefab installation cut-outs
- Prepared for the installation of pre-assembled cables



**Data sheet**  
**OpDAT fix<sup>2</sup> patch panel Prefab**  
**48xLC-D APC OS2 gray**

**Technical Data**

**General Data**

Fields of application	data center office areas structured building cabling interior Distributed building services
Features variant	Prefab
Design	Fixed installation
Mounting style	screwable
Transmission technology	Fiber optic
Port numbering	yes
Color housing	metal
Color front plate	RAL 7035 - light gray
Adapter color	green
Dimensions	
Dimension (L x W x H)	259 mm x 483 mm x 88 mm
Dimension (L x W x H)	10.197 in. x 19.016 in. x 3.465 in.
Inches	19 inches
Height unit	2RU
Installation depth	256 mm
Installation depth	10.079 in.
Fiber class	OS2
Mode type of the fiber	Singlemode
Shape	APC (Angled Physical Contact)
Labeling option	label strip / labeling strip

**Connections/interfaces**

Adapter type	LC-D
Cable access/outlet	several possibilities for cable entry on the back

**Mechanical data**

Cut-out	SC-S/LC-D/E2000-S
---------	-------------------

Data sheet  
**OpDAT fix<sup>2</sup> patch panel Prefab**  
**48xLC-D APC OS2 gray**

**Technical Data**

**Materials and material properties**

Material - Housing	sheet steel
Material - Housing finish	Zn (zinc)
Material - Front cover	sheet steel
Material - Front cover finish	powder-coated
RoHS	compliant, certificate see further information
REACH	compliant, 7439-92-1 – lead

**Classifications**

ETIM 8.0	EC001130
ETIM 9.0	EC001130
ETIM 10.0	EC001130

**Packing details**

Type of packaging	1 pc(s) / box
-------------------	---------------

**Application note**

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).

Data sheet  
**OpDAT fix<sup>2</sup> patch panel Prefab**  
**48xLC-D APC OS2 gray**

Page 4/5

P/N  
**1504807648-E**  
**EAN 4251394679419**  
2025/10/09  
Version: F

## Accessories

P/N	Designation
150240M20Z-E	OpDAT strain relief M20
150240M25Z-E	OpDAT strain relief M25
150240Z20Z-E	OpDAT strain relief for M20
1509010000-E	OpDAT splice tray for 12 splices, unequipped
1509010001-E	OpDAT splice tray with 1 crimp protection cover
1509010002-E	OpDAT splice tray with 2 splice protection cover
15090200-E	OpDAT cover for splice tray



Data sheet  
**OpDAT fix<sup>2</sup> patch panel Prefab**  
**48xLC-D APC OS2 gray**

Page 5/5

P/N  
**1504807648-E**  
EAN **4251394679419**  
2025/10/09  
Version: F

**Illustrations**

Dimensional drawing

