

Data sheet

OpDAT Prefab pulling aid IP50 size M

Page 1/3

P/N
152Z0050M-E

EAN 4251394670539

2025/07/24

Version: C

Illustrations



See enlarged drawings at the end of document

Product specification

- Sturdy corrugated tube for pulling in pre-assembled cables.
- for mounting on fixing sets or cable dividers
- Suitable for:
 - Universal cable up to 24 fibres
 - Outdoor cables up to 24 fibres
 - Mini breakout cables up to 24 fibres
 - Breakout cables up to 24 fibres



OpDAT Prefab pulling aid IP50 size M

P/N
152Z0050M-E

EAN 4251394670539

2025/07/24

Version: C

Technical Data

General Data

Mounting style	Accessories
Color	black
Dimensions	
Dimension (L x W x H)	130 cm x 37 mm x 37 mm
Dimension (L x W x H)	5.118 in. x 1.457 in. x 1.457 in.
Weight	130 g
Weight	0.2866 lb

Mechanical data

Mounting method	screwable
-----------------	-----------

Materials and material properties

Material	PA (polyamide)
Halogen free	yes

Environmental conditions

Temperature (min. - max.)	
Temperature - Operating °C	-40 °C - 120 °C
Temperature - Operating °F	-40 °F - 248 °F
Particulate ingress	IP5X

Classifications

ETIM 7.0	EC002609
ETIM 8.0	EC002609
ETIM 9.0	EC002609
ETIM 10.0	EC002609

Packing details

Type of packaging	1 pc(s) / box
-------------------	---------------

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).

Data sheet

Page 3/3

OpDAT Prefab pulling aid IP50 size M

P/N

152Z0050M-E

EAN 4251394670539

2025/07/24

Version: C

Accessories from

P/N	Designation
152U247JJ5020G	OpDAT Prefab Universal cable 24xOM4, LC-LC, 20 m, one-sided pulling aid IP50, class E _{ca}
152U247JJ5030G	OpDAT Prefab Universal cable 24xOM4, LC-LC, 30 m, one-sided pulling aid IP50, class E _{ca}
15CU247JJ5020G	OpDAT Prefab Universal cable 24xOM4, LC-LC, 20 m, one-sided pulling aid IP50, class C _{ca}
15CU247JJ5030G	OpDAT Prefab Universal cable 24xOM4, LC-LC, 30 m, one-sided pulling aid IP50, class C _{ca}

