

Data sheet


PC board jack M12, A-coded, 2-pole, IP67,
rear mounting, in individual parts

P/N
MMT371A915-0001
EAN 4251394632339
2026/08/03
Version: R


Illustrations



Dimensional drawing



Drill pattern



See enlarged drawings at the end of document

Product specification

- PC board jack M12
- rear mounting
- 2-pole, A-coded according to IEC 61076-2-101
- THR solderable
- Top entry
- Contact carriers black
- IP67 when plugged in
- in individual parts
- suitable for applications in the railway industry according to data sheet



Data sheet

Page 2/4

PC board jack M12, A-coded, 2-pole, IP67, rear mounting, in individual parts

P/N

MMT371A915-0001

EAN 4251394632339

2026/08/03

Version: R

Technical Data

General Data

Dimensions

Dimension (D x H)	Ø 21.5 mm x 20.5 mm
Dimension (D x H)	0.846 in. x 0.807 in.
Ports	Single port
Solderability	Acc. to IPC/JEDEC J-STD-020E-MSL 1
Coding	A-coded

Electrical characteristics

Rated voltage	250 V
Effective value of the withstand voltage	1.4 kV
Current carrying capacity at 40 °C	4 A
Insulation resistance	min. 100 MOhm
Overvoltage category	II
Degree of pollution	2

Mechanical data

Material

Material - Housing	CuZnPb
Material - Contact	CuZnPb
Contact surface	Ni + Au
Color	black
RoHS	compliant
Life - Number of mating cycles	>= 100
Protection category	IP65, IP67 when plugged in
Particulate ingress	IP6X when plugged in
Liquid ingress/immersion	IPX5, IPX7 when plugged in

Climatic properties

Temperature - Operating °C	-40 °C - 85 °C
Temperature - Operating °F	-40 °F - 185 °F



Data sheet

Page 3/4

PC board jack M12, A-coded, 2-pole, IP67, rear mounting, in individual parts

P/N

MMT371A915-0001

EAN 4251394632339

2026/08/03

Version: R

Technical Data

Approvals

Approval mark UL/CSA E305050

Standards/Regulations

Railway applications

Electronic equipment used on rolling stock	following to EN 50155:2021
Fire protection on railway vehicles	following to EN 45545-2:2020+A1:2023
Insulating body	PA UL 94 V0 complies with HL1-HL3; R26 according to EN 45545-2:2020+A1:2023
Flammable mass (g)	0.83 g
Sealings	Elastomer
Flammable mass (g)	0.18 g

Classifications

ETIM 7.0	EC002637
ETIM 8.0	EC002637

Packaging

Type of packaging 10 pc(s) / blister packaging

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).



Data sheet

Page 4/4

PC board jack M12, A-coded, 2-pole, IP67, rear mounting, in individual parts

P/N

MMT371A915-0001


EAN 4251394632339

2026/08/03

Version: R

Illustrations

Dimensional drawing



Drill pattern

