

Data sheet

OpDAT VADT plug-in 4xSC APC/SC APC OS2


Page 1/6

P/N
150C049HFFXXE


2026/08/27

Version: J

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- compact fiber optic termination unit for flush mounted outlets or cavity wall boxes
- Box ready for installation, pre-terminated with singlemode indoor cable and equipped with adapters including laser protection for the connection of up to four fiber optic patch cables.
- The second cable end is pre-assembled with fiber optic plugs, plug type selectable. To protect these connectors, nubbed foil, a retractable aid with IP50 or a Compact pulling aid is available.
- cable easy to mount on carton drum
- cable type: Mini Breakout Cable Compact, white, Ø 4.5 mm
- single mode fiber OS2, E9/125 µm, bend insensitive according to ITU-T G.657.A, compatible to G.652.D
- supplied with fixing material
- color box pure white (similar to RAL 9010)
- cable lengths: 2 to 100 m
- (replace XX in the part number by the length, for example 05=5 m, A0=100 m)
- all available variants can be created with the VADT configurator



Data sheet

Page 2/6

OpDAT VADT plug-in 4xSC APC/SC APC OS2

P/N
150C049HFFXXE

2026/08/27

Version: J

Technical Data

General Data

Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	wall outlet
Mounting style	AP
Transmission technology	Fiber optic
Color	white
Dimensions	
Dimension (L x W x H)	85 mm x 100 mm x 35 mm
Dimension (L x W x H)	3.346 in. x 3.937 in. x 1.378 in.
Mode type of the fiber	Singlemode
Fiber class	OS2
Shape	APC (Angled Physical Contact)
Fiber construction	9/125 µm

Connections/interfaces

Connector technology interface 1	SC
Connector technology interface 2	SC
Number of ports interface 1	4
Number of ports interface 2	4
Number of equipped ports interface 1	4
Number of ports interface 2 equipped	4
Number of blind	0
Cable sheath diameter (min. - max.)	
Cable sheath diameter	4.50
Cable sheath diameter	0.177



OpDAT VADT plug-in 4xSC APC/SC APC OS2

P/N
150C049HFFXXE

2026/08/27

Version: J

Technical Data

Electrical/ optical properties

Insertion loss	max. 0,3 dB
Return loss	min. 65 dB

Mechanical data

strain relief	aramide fibres
---------------	----------------

Materials and material properties

Material - Housing	Plastics
Material - Coupler housing	Plastics
Material - Sleeve	ceramic, slotted
Flame retardancy	yes
Halogen free	yes
RoHS	compliant

Standards/Regulations

Generic cabling systems

General requirements	ISO/IEC 11801-1
----------------------	-----------------

Lichtwellenleiter: LWL-Innenkabel

Sectional specification for classÂ B single-mode fibres	ISO/IEC 60793-2-50 type B.1.3 & B6_a
---	--------------------------------------

Optical fibers - Interconnecting devices and passive components - basic test and measuring methods

Fibre optic interconnecting devices and passive components - Insertion loss	IEC 61300-3-4
---	---------------

Fibre optic interconnecting devices and passive components - Return loss	IEC 61300-3-6
--	---------------

Fibre optic interconnecting devices and passive components - Visual inspection of plug end face	IEC 61300-3-35
---	----------------

ITU-T standard	ITU-T G.657.A1 compatible with ITU-T G.652.D
----------------	--

Classifications

ETIM 7.0	EC001409
ETIM 8.0	EC001409

Packing details

Type of packaging	1 pc(s) / box
-------------------	---------------



Data sheet

Page 4/6

OpDAT VADT plug-in 4xSC APC/SC APC OS2

P/N
150C049HFFXXE

2026/08/27

Version: J

Technical Data

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.



Data sheet

Page 5/6

OpDAT VADT plug-in 4xSC APC/SC APC OS2

P/N
150C049HFFXXE

2026/08/27

Version: J

Accessories

P/N	Designation
151P7EAEAXXE	OpDAT patch cord SC-S APC/SC-S APC OS2, white
151P7EAJAXXE	OpDAT patch cord SC-S APC/LC-S APC OS2, white
151P7EOEAXXE	OpDAT patch cord SC-S/SC-S APC OS2, white



Data sheet

Page 6/6

OpDAT VADT plug-in 4xSC APC/SC APC OS2


P/N
150C049HFFXXE

2026/08/27

Version: J

Illustrations

Dimensional drawing



© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

