

Data sheet

OpDAT ADT Prefab 4xE2000-S APC OS2


Page 1/5

P/N
1501105U04HC
EAN 4251394655383
2026/08/28
Version: G


Illustrations



Dimensional drawing



Drill pattern



See enlarged drawings at the end of document

Product specification

- compact, universal fiber optic termination unit for flush mounted outlets or cavity wall boxes, surface mounting or rail mounting
- to connect pre-terminated installation cables with mini breakout cables or to mount pigtails
- equipped with adapters with laser protection
- unequipped ports are closed with blind plugs
- possible cable entries: on the back, from above, from below, from the left or the right side
- with integrated clips for rail mounting in two directions
- pivoting, removable splice tray for up to 8 shrink splice protections
- cover removable without tool
- plug direction 90°
- color of the cover parts pure white RAL 9010
- variants: equipped with SC APC, SC UPC, LC-D APC or LC-D UPC, E2000-S APC adapters



Data sheet

Page 2/5

OpDAT ADT Prefab 4xE2000-S APC OS2

P/N
1501105U04HC
EAN 4251394655383
2026/08/28
Version: G

Technical Data

General Data	
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	wall outlet
Mounting style	surface mount, standard rail TH35
Transmission technology	Fiber optic
Color	pure white - RAL 9010
Dimensions	
Dimension (L x W x H)	85 mm x 100 mm x 35 mm
Dimension (L x W x H)	3.346 in. x 3.937 in. x 1.378 in.
Mode type of the fiber	Singlemode
Fiber class	OS2
Shape	APC (Angled Physical Contact)

Connections/interfaces	
Connector technology interface 1	E2000-S
Number of ports interface 1	4
Number of ports interface 2	4
Number of equipped ports interface 1	4
Number of ports interface 2 equipped	4
Number of ports with dust protection interface 1	4
Number of ports with dust protection interface 2	4
Module plug-in direction	straight
Cable access/outlet	rear, top, bottom, left or right
Mechanical data	
Cut-out	SC
Connector type	simplex



OpDAT ADT Prefab 4xE2000-S APC OS2

P/N
1501105U04HC
EAN 4251394655383
2026/08/28
Version: G

Technical Data

Materials and material properties

Material - Housing	ABS + PC
Material - Lower housing	ABS
Material - Coupler housing	Plastics
Material - Sleeve	ceramic, slotted
RoHS	compliant

Environmental conditions

Temperature (min. - max.)	
Temperature - Storage °C	-10 °C - 60 °C
Temperature - Storage °F	14 °F - 140 °F
Temperature - Operating °C	-10 °C - 60 °C
Temperature - Operating °F	14 °F - 140 °F
Particulate ingress	IP2X
Liquid ingress/immersion	IPX0

Classifications

ETIM 7.0	EC001409
ETIM 8.0	EC001409
ETIM 9.0	EC001409
ETIM 10.0	EC001409

Packing details

Type of packaging	1 pc(s) / box
-------------------	---------------

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.

Data sheet

Page 4/5

OpDAT ADT Prefab 4xE2000-S APC OS2

P/N

1501105U04HC

EAN 4251394655383

2026/08/28

Version: G


Accessories

P/N	Designation
15090304-I	OpDAT splice protection cover for 6 crimp splices
15090401-I	OpDAT crimp splice protection (150 pieces)



Illustrations

Dimensional drawing



Drill pattern

