

# Data sheet

**M12 Sensor/actuator cable, A-coded,  
M12 plug angled - free line end,  
shielded, 5-pole, PVC-C**

Page 1/6

P/N  
**142MMAD0XXX**


2026/09/10

Version: I


## Illustrations



Dimensional drawing



Wiring diagram



See enlarged drawings at the end of document

## Product specification

PVC-cable for measurement, control and sensor technology. Suitable for applications in dry areas on packaging machines, assembly and conveyor technology. High flexibility with unstressed movement (conditional drag chain application possible). Predestined for applications in food and beverage industry. Special features: seawater resistant, recyclable, LABS free, RoHs compliant, acid and alkali resistant, ozone resistant, UV resistant

- all available variants can be created with the configurator

## Data sheet

Page 2/6

# M12 Sensor/actuator cable, A-coded, M12 plug angled - free line end, shielded, 5-pole, PVC-C

P/N  
142MMAD0XXX

2026/09/10

Version: I

## Technical Data

| General Data                                  |                                               |
|-----------------------------------------------|-----------------------------------------------|
| Fields of application                         | Industrial Ethernet                           |
| Design                                        | Sensor/actuator connection cable M12, A-coded |
| Shielding                                     | shielded                                      |
| Transmission technology                       | Copper                                        |
| Color coding fiber/ wire(s)                   | brown, white, blue, black, gray               |
| Color                                         | gray                                          |
| Dimensions                                    |                                               |
| Dimension - Interface 1 (L x W x H)           | 33.5 mm x 37.5 mm x 15 mm                     |
| Dimension - Interface 1 (L x W x H)           | 1.319 in. x 1.476 in. x 0.591 in.             |
| Labeling option                               | identification label carrier                  |
| Connections/interfaces                        |                                               |
| Connector technology interface 1              | M12-plug angled                               |
| Connector technology interface 2              | free line end                                 |
| Coding interface 1                            | A-coded                                       |
| Number of positions/contacts interface 1      | 5                                             |
| Termination data, stranded wire (min. - max.) |                                               |
| Conductor cross section, stranded wire        | AWG 22/19                                     |
| Conductor cross section, stranded wire        | 0.34 mm <sup>2</sup>                          |
| Stranded wire structure                       | 19x0.15mm                                     |
| Cable sheath diameter (min. - max.)           |                                               |
| Cable sheath diameter                         | 5.5 mm                                        |
| Cable sheath diameter                         | 0.216 in.                                     |
| Electrical characteristics                    |                                               |
| Current carrying capacity                     | 4 A at 40 °C                                  |
| Rated voltage                                 | 60 V                                          |
| Insulation resistance                         | min. 100 MOhm                                 |



## Data sheet

Page 3/6

# M12 Sensor/actuator cable, A-coded, M12 plug angled - free line end, shielded, 5-pole, PVC-C

P/N  
142MMAD0XXX

2026/09/10

Version: I

## Technical Data

### Mechanical data

|                                  |          |
|----------------------------------|----------|
| Life - Number of mating cycles   | min. 100 |
| Maximum operating bending radius | 55 mm    |
| Alternating bending radius       | 55 mm    |

### Materials and material properties

#### Cable

|                                 |             |
|---------------------------------|-------------|
| Material - Conductor            | Cu (copper) |
| Material - Conductor Insulation | PVC         |
| Material - Cable jacket         | PVC         |

#### Interface 1

|                                         |                |
|-----------------------------------------|----------------|
| Material - Body interface 1             | Plastics       |
| Material - Contact interface 1          | CuSn           |
| Material - Contact finish interface 1   | Au (gold)      |
| Material - Contact carriers interface 1 | Plastics       |
| Material - Union nut interface 1        | CuZnPb (brass) |
| Material - Union nut finish interface 1 | Ni (nickel)    |

UV-resistance yes

RoHS compliant

### Environmental conditions

#### Temperature (min. - max.)

|                               |                 |
|-------------------------------|-----------------|
| Temperature - Operating °C    | -25 °C - 80 °C  |
| Temperature - Operating °F    | -13 °F - 176 °F |
| Temperature - Installation °C | 0 °C - 80 °C    |
| Temperature - Installation °F | 32 °F - 176 °F  |

Particulate ingress interface 1 IP6X when plugged in

Liquid ingress/immersion interface 1 IPX5, IPX7, IPX8 when plugged in

Pollution degree interface 1 3



## Data sheet

Page 4/6

**M12 Sensor/actuator cable, A-coded,  
M12 plug angled - free line end,  
shielded, 5-pole, PVC-C**

**P/N**  
**142MMAD0XXX**

2026/09/10

Version: I

## Technical Data

### Approvals

UL listed (file no.) Approval pending

### Standards/Regulations

Connectors for electronic equipment

circular connector DIN EN 61076-2-101

### Classifications

ETIM 7.0 EC001855

ETIM 8.0 EC001855

### Packing details

Type of packaging 1 pc(s) / plastic bag

### Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.

## Data sheet

Page 5/6

**M12 Sensor/actuator cable, A-coded,  
M12 plug angled - free line end,  
shielded, 5-pole, PVC-C**


P/N  
**142MMAD0XXX**

2026/09/10


Version: I

## Illustrations

### Dimensional drawing



### Wiring diagram



Data sheet

Page 6/6

**M12 Sensor/actuator cable, A-coded,  
M12 plug angled - free line end,  
shielded, 5-pole, PVC-C**

**P/N**  
**142MMAD0XXX**

2026/09/10

Version: I

## Illustrations

Principle diagram

