

Data sheet

KRA-S-F10/21-21, 2 changeover contacts, 24 V AC/DC

Page 1/7

P/N
11070713

EAN 4250184123101


2026/09/23

Version: J


Illustrations



Dimensional drawing



Wiring diagram



See enlarged drawings at the end of document

Product specification

Coupling devices are used to electrical isolation between logic and load.

- Connection with spring-clamp terminal
- Additional terminals for jumper
- Test contacts for each terminal
- safe separation
- with manual control level

Data sheet

Page 2/7

KRA-S-F10/21-21, 2 changeover contacts, 24 V AC/DC

P/N

11070713

EAN 4250184123101

2026/09/23

Version: J

Technical Data

Supply

Operating voltage	24 V AC/DC -15% ... +10%
Power consumption (max.)	16 mA
Response time typical	10 ms
Release time typical	5 ms

Manual control level

Mechanical life	1x10 ³ switching cycles
Switching capacity (max.)	24 V AC/DC / 50 mA
Switching capacity (min.)	3 V AC/DC / 50 µA
Test voltage	100 V, 50 Hz, 1 min

Outputs

Contacts	2 changeover contacts
Contact material	AgSnO ₂
Switching voltage (max.)	250 V AC
Continuous Current	3 A
Switching frequency	300 switching cycles/h
Breaking capacity (resistive load)	
Mechanical life	1x10 ⁷ switching cycles
Electrical life	1x10 ⁵ switching cycles
Indicator	green LED

Insulation coil - contact set

Nominal voltage of the power supply system	230 / 400 V AC
Overvoltage category	III II
Degree of pollution	2 2
Rated test voltage	4 kV 2.5 kV
Type of insulation	basic insulation reinforced insulation

Housing

Dimensions	
Dimension (W x H x D)	11.2 mm x 87.5 mm x 60 mm
Dimension (W x H x D)	0.441 in. x 3.445 in. x 2.362 in.
Weight	43 g
Mounting style	Standard rail TH35
Mounting position	any



Data sheet

Page 3/7

KRA-S-F10/21-21, 2 changeover contacts, 24 V AC/DC

P/N

11070713

EAN 4250184123101

2026/09/23

Version: J

Technical Data

Housing

Apposition	without distance
Connection type	Spring clamp terminal blocks

Terminal blocks

Wire cross section solid	0.08 mm ² - 2.5 mm ² / AWG 28-14
Wire cross section multi	0.08 mm ² - 2.5 mm ² / AWG 28-14
Wire cross section with wire ferrule	0.14 mm ² - 1.5 mm ² / AWG 26-16
Stripping length (min.)	10 mm

Material

Material - Housing	Polyamid 6.6 V0
Color	gray
Material - Terminal block	Polyamid 6.6 V0

Protection category according to IEC 60529

Protection category - housing (acc. to IEC 60529)	IP40
---	------

Climatic Data

Operating	
Temperature - Operating °C	-20 °C - 55 °C
Temperature - Operating °F	-4 °F - 131 °F
Relative humidity	max. 85 % non-condensing
Storage	
Temperature - Storage °C	-25 °C - 70 °C
Temperature - Storage °F	-13 °F - 158 °F

Power loss

Power loss (typical)	0.5 W
----------------------	-------

Classifications

ETIM 7.0	EC001437
ETIM 8.0	EC001437
ETIM 9.0	EC001437
ETIM 10.0	EC001437



Data sheet

Page 4/7

KRA-S-F10/21-21, 2 changeover contacts, 24 V AC/DC

P/N

11070713

EAN 4250184123101

2026/09/23

Version: J

Technical Data

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.



Data sheet

Page 5/7

KRA-S-F10/21-21, 2 changeover contacts, 24 V AC/DC

P/N

11070713

EAN 4250184123101

2026/09/23

Version: J


Accessories

P/N	Designation
110728	Connecting bridge, 10 pole
110729	Labeling plate



Illustrations

Dimensional drawing



Wiring diagram

11	21	A1 - A2 operating voltage A2-A3 operating voltage 11 - 12 - 14 21 - 22 - 24 output contact 2 changeover contacts
A1	A3	
A1	A2	
12	22	
14	24	

KRA-S-F10/21-21, 2 changeover contacts, 24 V AC/DC

P/N
11070713

EAN 4250184123101

2026/09/23

Version: J

Illustrations

Circuit diagram

