

Data sheet

ASD-C18

Page 1/7

P/N

110270

EAN 4250184120940


2026/09/23

Version: J


Illustrations



Dimensional drawing



Wiring diagram



See enlarged drawings at the end of document

Product specification

Monitoring relay for monitoring asymmetry, phase failure, phase sequence errors, overvoltage and undervoltage of a three-phase connection. With external fault acknowledgement.

- Connection with screw type terminal blocks
- Adjustable response delay
- Adjustable asymmetry
- Selectable fault memory
- 7-segment display

Data sheet

ASD-C18

Page 2/7

P/N
110270
EAN 4250184120940
2026/09/23
Version: J

Technical Data

Supply

Operating voltage	230 V AC -15% ... +10%
Frequency range	50 Hz
Power consumption (max.)	15 mA
Duty cycle relative	100 %

Inputs

Monitoring voltage (L1, L2, L3)	3 x 230/400 V AC, 50 Hz
Response delay	0.1 s - 9.9 s, adjustable
Confirmation time, adjustable	0,1 ... 9,9 min.
Asymmetry, adjustable	5 ... 20 %
Switching hysteresis	20 %
Measurement cycle	max. 100 ms
Temperature error	<= 0.06 %/°C
Measurement error within the operating voltage	<= 5 %

Outputs

Contacts	2 changeover contacts
Contact material	AgNi
Switching voltage (max.)	250 V AC
Continuous Current	8 A
Pick-up delay	230 V~ 6 A AC1
Switch-off delay	230 V~ 3 A AC3
Switching frequency	360 switching cycles/h
Mechanical life	3x10 ⁷ switching cycles
Electrical life	1x10 ⁵ switching cycles
Indicator	green LED

Housing

Dimensions	
Dimension (W x H x D)	50 mm x 69.3 mm x 60 mm
Dimension (W x H x D)	1.969 in. x 2.728 in. x 2.362 in.
Weight	200 g
Mounting style	Standard rail TH35
Mounting position	any

Data sheet ASD-C18

Page 3/7

P/N
110270
EAN 4250184120940
2026/09/23
Version: J

Technical Data

Housing

Apposition	without distance
Connection type	Screw type terminal blocks

Terminal blocks

Wire cross section solid	0.34 mm ² - 2.5 mm ² / AWG 22-12
Wire cross section multi	0.25 mm ² - 2.5 mm ² / AWG 22-12
Wire cross section with wire ferrule	0.25 mm ² - 2.5 mm ² / AWG 22-12
Screw torque (max.)	0.5 Nm
Stripping length (min.)	8 mm

Material

Material - Housing	Polyamid 6.6 V0
Color	gray
Material - Terminal block	Polyamid 6.6 V0
Material - Covers	Polycarbonat

Protection category according to IEC 60529

Protection category - housing (acc. to IEC 60529)	IP40
Protection category - terminal blocks (acc. to IEC 60529)	IP20

Climatic Data

Operating	
Temperature - Operating °C	-5 °C - 55 °C
Temperature - Operating °F	23 °F - 131 °F
Relative humidity	max. 85 % non-condensing

Storage

Temperature - Storage °C	-20 °C - 70 °C
Temperature - Storage °F	-4 °F - 158 °F

Power loss

Power loss (typical)	5 W
----------------------	-----



Data sheet
ASD-C18

Page 4/7

P/N
110270
EAN 4250184120940
2026/09/23
Version: J

Technical Data

Classifications

ETIM 7.0	EC001441
ETIM 8.0	EC001441
ETIM 9.0	EC001441
ETIM 10.0	EC001441

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.




Data sheet **ASD-C18**

Page 5/7


P/N
110270
EAN 4250184120940
2026/09/23
Version: J

Illustrations

Dimensional drawing



Wiring diagram



Data sheet
ASD-C18

Page 6/7

P/N
110270


EAN 4250184120940

2026/09/23


Version: J

Illustrations

Schaltbeispiel




Function diagram



Illustrations

Function diagram



Function diagram

