

Product information – OpDAT PF



Product specification

- > FO patch panel for 19-inch systems, 1 rack unit (RU)
- > Service-friendly mounting and connection
- > Light construction with aluminium front panel and housing
- > Anodised front plates available in grey (RAL 7035) or black (RAL 9005)
- > Front panels with labelling fields
- > Unused cutouts in the front plate are covered by blank plugs
- > Available with the following adapters: LC-, SC-duplex adapters, E2000-simplex adapters. Other types available on request
- > Pigtails are available with fiber types OM3, OM4, OM5 and OS2. All pigtails are inspected and cleaned before inserted into the adapters according to IEC 61300-3-35
- > Now also available with pigtails of quality class Grade B. Particularly low insertion loss values are achieved by selecting and processing the connector ferrules.
- > All standard patch panels are available with holders for crimpsplice or shrink splice protections
- The rear panel has 10 options for cable insertion: 4x PG13.5, 2x PG16/M20, 2x PG21/M25, U-shaped cutouts for VIK

P Cabling

Equipment variants

OpDAT PF patch fields are available in 2 equipment variants.


PRODUCT NAME	VARIANT SPLICE	VARIANT VIK	
		tittenstatitititititititititititititititititit	
Properties	 > Equipped with adapters and pigtails > Pigtails are stored ready for splicing in splice trays with splice holders > Pigtail connectors are cleaned and inserted into adapters, assignment is made according to the IEC 60304 colour code 	 > Equipped with adapters > Prepared for tool-free fixing of pre-assembled installation cables (OpDAT VIK) in U-shaped cutouts 	
Accessories	 > One cable gland M20 > Additional screw connections are available as accessories 	 > Two retaining plates > Additional retaining plates are available as accessories 	

Technical data

VARIANT	VARIANT SPLICE with pigtails and adapters		VARIANT VIK
Properties			
Equipped with	adapters	pigtails	adapters
SC-Duplex	6 12	12 24	6 12
LC-Duplex	6 12 24	12 24 48	6 12 24
ST-Simplex	6 12 24	6 12 24	6 12 24
E2000-Simplex	12 24	12 24	12 24
Dimension for fixation			465 mm
Installation dimension (L x H x D)			384 x 1RU x 240 mm

ACCESSORIES		P/N
	M20 (clamping range 7 to 12 mm)	150811M20-E
Cable gland	M20 (clamping range 4 to 13 mm)	150811M20C-E
	M25 (clamping range 10 to 16 mm)	150811M25-E
Retaining plate VIK		15081106-E
		15090401-E (PU 12 pieces)
Crimp splice protection		15090401-I (PU 150 pieces)
Shrink splice protection		15090402-I (PU 12 pieces)

Ordering information





You can put together all available combinations using our patch field configurator: www.metz-connect.com/configurator



METZ CONNECT GmbH

Im Tal 2 78176 Blumberg Germany

Phone +49 7702 533-0 Fax +49 7702 533-189

info@metz-connect.com www.metz-connect.com

METZ CONNECT USA Inc.

200 Tornillo Way Tinton Falls, NJ 07712 USA Phone +1-732-389-1300 Fax +1-732-389-9066

METZ CONNECT France SAS

28, Rue Schweighaeuser 67000 Strasbourg France Phone +33 38 86 17073 Fax +33 38 86 19473

METZ CONNECT AUSTRIA GmbH

c/o German chamber of commerce in Austria Schwarzenbergplatz 5, Top 3/1 1030 Vienna Austria Phone +43 1 227 12 64 Fax +43 1 227 12 66

METZ CONNECT Zhongshan Ltd.

Ping Chang Road Ping Pu Industrial Park Sanxiang Town Zhongshan City, 528463 Guangdong Province China Phone +86 760 86365055 Fax +86 760 86365050

METZ CONNECT Asia Pacific Ltd.

Suite 1803, 18/F Chinachem Hollywood Centre, 1 Hollywood Road, Central Hong Kong Phone +852 26 027 300 Fax +852 27 257 522



